



Nylon NPT Coupling

FNPT Size	Part Number	◆ Stk	Std Price	Bulk Price	Bulk Pkg
1/8"	N245-013NY	C	\$ 7.86	\$ 6.55	10
1/4"	N245-025NY	C	7.86	6.55	10
3/8"	N245-038NY	N	7.86	6.55	10
1/2"	N245-050NY	C	8.28	6.90	10
3/4"	N245-075NY	N	8.28	6.90	10
1"	N245-100NY	C	8.56	7.13	10

*Other sizes available



Nylon Reducer Bushing

MNPT Size	FNPT Size	Part Number	◆ Stk	Std Price	Bulk Price	Bulk Pkg
NPT Thread						
1/4"	1/8"	N260-025-013NY	C	\$ 3.38	\$ 2.81	10
3/8"	1/8"	N260-038-013NY	C	3.14	2.61	10
3/8"	1/4"	N260-038-025NY	C	2.86	2.38	10
1/2"	1/4"	N260-050-025NY	C	2.98	2.48	10
1/2"	3/8"	N260-050-038NY	C	3.12	2.60	10
3/4"	3/8"	N260-075-038NY	N	3.54	2.95	10
3/4"	1/2"	N260-075-050NY	C	3.22	2.68	10
1"	1/2"	N260-100-050NY	N	4.76	3.96	10
1"	3/4"	N260-100-075NY	N	4.56	3.80	10

NPT x UNF 1/4-28 Thread

1/8"	UNF N260-013-UNF1/4-28NY	C	\$ 2.46	\$ 1.89	10
1/4"	UNF N260-025-UNF1/4-28NY	C	1.46	1.12	10

NPT x UNF 10-32 Thread

1/8"	UNF N260-013-UNF10-32NY	C	\$ 2.46	\$ 1.89	10
1/4"	UNF N260-025-UNF10-32NY	C	2.71	2.08	10

*Other sizes available



Nylon NPT Reducer Coupling

FNPT Size	FNPT Size	Part Number	◆ Stk	Std Price	Bulk Price	Bulk Pkg
1/4"	1/8"	N250-025-013NY	C	\$ 7.86	\$ 6.55	10
3/8"	1/4"	N250-038-025NY	C	7.86	6.55	10
1/2"	3/8"	N250-050-038NY	C	8.22	6.85	10
3/4"	3/8"	N250-075-038NY	N	8.61	7.17	10
3/4"	1/2"	N250-075-050NY	N	8.61	7.17	10

*Other sizes available



Nylon 45° NPT Street Elbow

MxFNPT Size	Part Number	◆ Stk	Std Price	Bulk Price	Bulk Pkg
1/4"	N220-025NY	C	\$ 7.67	\$ 6.39	10
1/2"	N220-050NY	N	POR	POR	10
3/4"	N220-075NY	C	7.98	6.65	10

*Other sizes available

Nylon NPT Manifold



For more information refer to the:
Manifolds in this Section - pg.460

THREADED SIGHT GLASSES



N200 Male NPT Threaded



N200V Victaulic Grooved

Clear Polycarbonate Sight Glass

This durable sight glass is generally used by pumpers and water haulers to see what is flowing through heat-treaters, separators and storage tank drain lines at all times. They are **NOT** designed for pressure applications, only drain lines, and they are **NOT** for use with aromatic hydrocarbons, esters, strong acids, and various concentrations of solvents or ketones. The sight glass is made from a tough, shatter-resistant polycarbonate (30 times the impact resistance of safety glass), withstands prolonged exposure to UV rays, and can be used in temperatures ranging from -101°C to 74°C (-150°F to 165°F). Use an oily rag to clean (avoid scratching sight glass) and always place a pipe wrench on the metal connections and not the sight glass when tightening.

Size	Part #	Stk	Price/ea	Pkg
Male NPT (8" long)				
2"	N200-200-800PC	C	\$ 168.59	1
3"	N200-300-800PC	C	230.01	1
4"	N200-400-800PC	C	331.21	1
Victaulic Groove (8" long)				
2"	N200V-200-800PC	C	\$ 152.09	1
3"	N200V-300-800PC	N	225.91	1
4"	N200V-400-800PC	N	297.71	1



Fused Window Sight Glass

Fused Window Sights allow visual observation of liquid levels and their condition. They can be used to display fluid motion or mechanical movements, as well as to view and perform tests in a safe enclosure. Specific uses include fluid sighting on hydraulic tanks, pressure vessels, reservoirs, packaged power equipment, hydraulic lines and dipping. Their use can be applied to any application where oil or fluid inspection is essential. Two or more sights can be mounted so as to indicate high, low or in-between levels.

These window sights may be mounted into any corresponding pipe thread. The body is constructed with plated steel (other body materials are available upon request). The glass sight is a polycarbonate material fused to the steel body, creating a leak free seal. The window sight withstands up to 125 psi and temperatures up to 121°C (250° F).

Size	Part #	Stk	Price/ea	Pkg
1/4" NPT	NSGNPT-04	C	\$ 24.76	1
3/8"	NSGNPT-06	C	29.39	1
1/2"	NSGNPT-08	C	30.79	1
3/4"	NSGNPT-12	C	38.05	1
1"	NSGNPT-16	C	49.83	1
1-1/4"	NSGNPT-20	C	86.88	1
1-1/2"	NSGNPT-24	C	103.00	1
2"	NSGNPT-32	C	123.12	1

