

Compressor Air Receiver Check Valves

These are used to control the flow of air from the compressor into a receiver. When the compressor reaches unload pressure, the check valve closes and prevents backflow from the receiver. Max 500 psi & max temperature +450°F. They have a 1/8" NPT unloader port.

Inlet FNPT	Outlet NPT	Part Number	CFM	Stk	Price Each
1/4"	1/4"	NCLB-025	12	C	\$ 32.23
3/8	3/8	NCLB-038	15	C	33.10
1/2	1/2	NCLB-050	20	C	43.13
3/4	3/4	NCLB-075	30	C	56.42
3/4	3/4	NCLBH-075	60	C	117.55
1	1	NCLB-100	60	C	297.27
1-1/2	1-1/2	NCLB-150	60	N	81.96
1-1/2	1-1/2	NCLBH-150	90	N	396.19



347

Compressor Bronze Spring Check Valve

These spring check valves are designed for higher flow compressed air systems, and typically used for the air compressor discharge lines; however, they can be used for water as well. They have a bronze body with stainless steel spring, 15% glass filled PTFE poppet, a machined brass cap & 1/8" NPT threaded bottom port. Maximum pressure rating 250psi. Cracking pressure approx 3psi. Maximum temperature rating +232°C (450°F). Repair kits available upon request (N10072RK-Size).

FNPT Size	Part Number	♦ Stk	Std Each	Bulk Each	Bulk Pkg
1/4"	N10072-025BR	C	\$ 36.05	\$ 32.77	5
3/8	N10072-038BR	C	43.31	39.37	5
1/2	N10072-050BR	C	77.47	70.42	5
3/4	N10072-075BR*	C	76.75	69.77	5
1	N10072-100BR	C	160.37	145.79	5
1-1/4	N10072-125BR	C	238.13	216.48	5
1-1/2	N10072-150BR	N	255.23	232.02	5

*Available in retail display packs (prefix X).

**Other Sizes Available



Compressor Start-Up Unloader Valves

These are used in conjunction with check valves or unloader valves that have an air unloader port. They help the compressor start without a load (removes the air in the discharge line). They close at 30-40 psi.

Male NPT	Part #	Stk	Price/Ea
1/8	NSU3-013	C	\$ 7.42
1/4	NSU3-025	C	11.16

NCLS-
Male x Male




NCLSF-
Female x Male




In-Line Compact NPT Brass Check Valves

Inlet	Outlet	Part #	Stk	Price/Ea
1/4" MNPT	1/4" MNPT	NCLS-025-025	C	\$ 17.79
1/4 FNPT	1/4 MNPT	NCLSF-025-025	C	31.28
1/4 MNPT	1/2 MNPT	NCLS-025-050	C	28.61
3/8 MNPT	3/8 MNPT	NCLS-038-038	C	27.98
3/8 MNPT	1/2 MNPT	NCLS-038-050	C	31.29



NTCV
Available in brass
body with plated
steel tip, or brass
tip (suffix BR)



NTCVT
Available in brass
body with plated
steel tip, or brass
tip (suffix BR)

330A

Compressor Vertical In-Tank Check Valves

These are designed for use on the discharge line of lubricated or non-lubricated air compressors to prevent back flow from the air tank. They have a glass-filled PTFE Disc and a 1/8" NPT side unloader port.

Inlet	Outlet MNPT	Part Number	♦ SCFM	Price Stk Each
NPT Brass Body with Plated Steel Tip				
3/8" FNPT	1/2"	NTCV-038-050	20	C \$ 15.27
1/2	1/2	NTCV-050-050	20	C 25.23
1/2	3/4	NTCV-050-075	30	C 26.49
3/4	3/4	NTCV-075-075	30	B 29.87
3/4	1	NTCV-075-100	60	C 49.95
3/4	1-1/2	NTCV-075-150	150	C 171.58
1	1	NTCV-100-100	60	C 50.26
NPT Brass Body with Brass Tip				
1/2" FNPT	1/2"	NTCV-050-050BR	20	B \$ 28.38
1/2	3/4	NTCV-050-075BR	30	C 30.86
3/4	3/4	NTCV-075-075BR	30	B 33.87
3/4	1	NTCV-075-100BR	60	C 54.28
3/4	1-1/2	NTCV-075-150BR	150	C 179.95
1	1	NTCV-100-100BR	60	C 55.74
1-1/4	1-1/4	NTCV-125-125BR	130	C 112.12
1-1/2	1-1/2	NTCV-150-150BR	150	C 189.44
Male Compression Tube Plated Steel				
3/8" Tube	3/8"	NTCVT-038-038	20	C \$ 16.16
1/2	1/2	NTCVT-050-050	20	C 23.45
3/4	3/4	NTCVT-075-075	30	N 26.10
Male Compression Tube Brass				
1/2" Tube	3/8"	NTCVT-050-038BR	20	C \$ 21.20
1/2	1/2	NTCVT-050-050BR	20	C 26.10
3/4	3/4	NTCVT-075-075BR	30	N 30.86
3/4	1	NTCVT-075-100BR	60	N 53.07

Industrial, Faucets, Strainers & Foot Valves

P2

