

NL3103 is a low pressure agricultural fuel hose designed for use on gravity tanks, manual barrel pumps, electric pumps, drums, and storage tanks on farm, construction, and industrial sites where a ULC approved hose is **not** required. It is suitable for both leaded and unleaded fuel, alcohol extended fuels, diesel, E85 and oils with up to a 50% aromatic content. NL3103 incorporates a small static wire in its wall which is to be grounded to the fitting to reduce the risk of a spark being generated by static electricity caused by the movement of the fuel. It should be noted that our NL3103 is made of higher grade compounds as compared to other imitations on the market which harden and crack prematurely.



Supplied with anti-static wire which must be grounded to couplings.

Temperature Range: -37°C (-35°F) to +82°C (180°F)

Construction: Tube: Black nitrile. Cover: Smooth, black nitrile blend. Reinforcement: Textile braid with an anti-static wire.


Typical Fittings: N90 Zinc Farm Tank, N98/N99 Chrome Curb Pump (low pressure/gravity only).

Inside Diameter	Part #	Outside Diameter	W.Pressure @20°C(70°F)	Bend Radius	Weight lbs/ft	♦ Stock	Regular Price/ft	Std 50' Increments	Bulk Price/ft	Bulk Length
3/4"	NL3103-075	1.13"	100 psi	-	.37	B	\$ 4.31	\$ 3.65	\$ 3.31	500 ft
1"	NL3103-100	1.50	100	-	.60	A	5.67	4.80	4.36	45

Size	Part #	Weight	♦ Stk	1-9 Assorted	10+ Assorted
3/4" 10ft	A3103075X10-160	3.9 lbs	C	\$ 64.53	\$ 61.45
12	A3103075X12-160	4.6	C	71.47	68.06
15	A3103075X15-160	5.6	C	81.87	77.97
20	A3103075X20-160	7.6	C	97.44	92.80
25	A3103075X25-160	9.5	C	114.47	109.01
1" 10ft	A3103100X10-160	6.2	C	81.36	77.48
12	A3103100X12-160	7.4	C	88.92	84.68
15	A3103100X15-160	9.2	C	102.45	97.57
20	A3103100X20-160	12.2	C	123.88	117.98
25	A3103100X25-160	15.2	C	146.23	139.26

Z07

One end quality control marked to ensure proper ground



Zinc Farm Tank Ends Suffix (-160)



Petroleum Delivery & Dispensing

